

RoHS

CUST INFORMATION.		
PART NO. NA	DRAWING NO. NA	REV. NA

DRAWING NO.	NA
-------------	----

Specifications:

- 1.Current rating:1A AC,DC
- 2.Voltage rating:125V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:20mΩMax.
- 5.Insulation resistance:100MΩMin.
- 6.Withstanding voltage:500V AC/minute
- 7.Material:PA66 UL94V-0
- 8.Bill Of Part No.:

FU1251H-XP-X-HF

Pin: _____	Material Color
2	A : White
3	B : Black
4	C : Red
.	D : Orangr
.	E : Yellow
.	F : Green
	.
	.
	.

17.50	20.50	19.20	15
16.25	19.25	17.95	14
15.00	18.00	16.70	13
13.75	16.75	15.45	12
12.50	15.50	14.20	11
11.25	14.25	12.95	10
10.00	13.00	11.70	9
8.75	11.75	10.45	8
7.50	10.50	9.20	7
6.25	9.25	7.95	6
5.00	8.00	6.70	5
3.75	6.75	5.45	4
2.50	5.50	4.20	3
1.25	4.25	2.95	2
A	B	C	PIN

Technical drawing of a mechanical part with dimensions:

- Top horizontal dimension: 3.2 ± 0.25
- Left vertical dimension: 4.0 ± 0.25
- Bottom horizontal dimension: 2.3 ± 0.15

 2.3 ± 0.15

TOLERANCE	
X.	X.XXX ± 0.1
X.X ± 0.30	
X.XX ± 0.20	Angular $\pm 2^\circ$
	UNIT: mm
DWG TYPE.	
Customer Drawing	

UNIT:
mm

PART NO.
FU1251H-XP-X-HF

东莞市福朗连接器制造有限公司 DongGuan FuLang Connector Manufacturing Co., LTD	
TITLE.	1.25mm Pitch Wire To Board Housing

CHECKED BY	
---	---

PAGE	10F1
------	------

REV.	
A	

8		For New Drawing	GuobaoLi	2017.12.05
REV.	ECN NO	REVISION RECORD	DRAW	DATE

2

4

5

6 QMI-P17-06-05

6 QMI-P17-06-05