

RoHS

CUST INFORMATION.

PART NO.	DRAWING NO.	REV.
NA	NA	NA

Specifications:

- 1.Current rating:1A AC,DC
- 2.Voltage rating:125V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:20mΩMax.
- 5.Insulation resistance:100MΩMin.
- 6.Withstanding voltage:500V AC/minute
- 7.Material:PA66 UL94V-0


8.Bill Of Part No.:

FU1251H-XP-X-HF

Pin:	Material Color
2	A : White
3	B : Black
4	C : Red
.	D : Orangr
.	E : Yellow
.	F : Green
.	.
.	.

9.Ordering Information & Dimensions

17.50	22.35	16.29	15
16.25	21.10	15.04	14
15.00	19.85	13.79	13
13.75	18.60	12.54	12
12.50	17.35	11.29	11
11.25	16.10	10.04	10
10.00	18.85	8.79	9
8.75	13.60	7.54	8
7.50	12.35	6.29	7
6.25	11.10	5.04	6
5.00	9.85	3.79	5
3.75	8.60	2.54	4
2.50	7.35	---	3
1.25	6.10	---	2
A	B	C	PIN

TOLERANCE		PART NO.	东莞市福朗连接器制造有限公司 DongGuan FuLang Connector Manufacturing Co., LTD		
X.	X.XXX ±0.1	FU1253H-XP-X-HF	DRAWING NO. C-FU1253H-XP-X-HF		
X.X ±0.30					
X.XX ±0.20	Angular ±2°		TITLE. 1.25mm PITCH WIRE TO BOARD HOUSING		
	UNIT: mm				
DWG TYPE. Customer Drawing		APPROVED BY	CHECKED BY	DRAWN BY	PAGE 1 OF 1
					SCALE 10: 1
					REV. A

8		For New Drawing	GuobaoLi	2017.12.05
REV.	ECN NO	REVISION RECORD	DRAW	DATE

1 2 3 4 5 6

A

B

C

D

A

B

C

D

6 QMI-P17-06-05