

RoHS

CUST INFORMATION.

PART NO.	DRAWING NO.	REV.
NA	NA	NA

Specifications:

- 1.Current rating:2A AC,DC
- 2.Voltage rating:100V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:10mΩMax.
- 5.Insulation resistance:1000MΩMin.
- 6.Withstanding voltage:800V AC/minute
- 7.Material:PA66 UL94V-0
- 8.Bill Of Part No.:

FU2004H-XP-X-HF

Pin:	Material Color
2	A : White
3	B : Black
4	C : Red
.	D : Orangr
.	E : Yellow
.	F : Green
.	.
.	.

9.Ordering Information & Dimensions

28.00	31.80	15	14.00	17.80	8
26.00	29.80	14	12.00	15.80	7
24.00	27.80	13	10.00	13.80	6
22.00	25.80	12	8.00	11.80	5
20.00	23.80	11	6.00	9.80	4
18.00	21.80	10	4.00	7.80	3
16.00	19.80	9	2.00	5.80	2
A	B	PIN	A	B	PIN

TOLERANCE		PART NO.	东莞市福朗连接器制造有限公司 DongGuan FuLang Connector Manufacturing Co., LTD		
X.	X.XXX ±0.1	FU2004H-XP-X-HF			
X.X	±0.30	DRAWING NO.	TITLE.		
X.XX	±0.20				
UNIT:		C-FU2004H-XP-X-HF	2.00mm Pitch Wire To Board Housing		
mm		APPROVED BY	CHECKED BY	DRAWN BY	PAGE
DWG TYPE.				10F1	
Customer Drawing				SCALE	
				5: 1	
				REV.	
				A	

A		For New Drawing	GuobaoLi	2017.12.05
REV.	ECN NO	REVISION RECORD	DRAW	DATE

