

RoHS

CUST INFORMATION.

PART NO.	DRAWING NO.	REV.
NA	NA	NA

Specifications:

- 1.Current rating:2A AC,DC
- 2.Voltage rating:125V AC,DC
- 3.Temperature range:-40°C~+105°C
- 4.Contact resistance:20mΩMax.
- 5.Insulation resistance:1000MΩMin.
- 6.Withstanding voltage:800V AC/minute
- 7.Material:PA66 UL94V-0
- 8.Bill Of Part No.:

FU2003H-XP-X-HF

Pin:	Material Color
2	A : White
3	B : Black
4	C : Red
.	D : Orangr
.	E : Yellow
.	F : Green

DIM A±0.20

DIM B±0.25

DIM C±0.30

3.4±0.2

3.7

5.9±0.2


3.8±0.2

9.Ordering Information & Dimensions

28.00	31.10	32.20	15	14.00	17.10	18.20	8
26.00	29.10	30.20	14	12.00	15.10	16.20	7
24.00	27.10	28.20	13	10.00	13.10	14.20	6
22.00	25.10	26.20	12	8.00	11.10	12.20	5
20.00	23.10	24.20	11	6.00	9.10	10.20	4
18.00	21.10	22.20	10	4.00	7.10	8.20	3
16.00	19.10	20.20	9	2.00	5.10	6.20	2
A	B	C	PIN	A	B	C	PIN

TOLERANCE

X.	X.XXX ±0.1
X.X ±0.30	
X.XX ±0.20	Angular ±2°



UNIT:
mm

DWG TYPE.

Customer Drawing

PART NO.

FU2003H-XP-X-HF

DRAWING NO.

C-FU2003H-XP-X-HF

APPROVED BY

CHECKED BY

DRAWN BY

PAGE

1OF1

REV.

SCALE

5: 1

A

东莞市福朗连接器制造有限公司
DongGuan FuLang Connector Manufacturing Co., LTD

TITLE.

2.00mm Pitch Wire To Board Housing

A		For New Drawing	GuobaoLi	2017.12.05
REV.	ECN NO	REVISION RECORD	DRAW	DATE

QMI-P17-06-05