

RoHS

CUST INFORMATION.

PART NO.	DRAWING NO.	REV.
NA	NA	NA

Specifications:

- 1.Current rating:3A AC,DC
- 2.Voltage rating:250V AC,DC
- 3.Temperature range:-40℃~+105℃
- 4.Contact resistance:20mΩMax.
- 5.Insulation resistance:1000MΩMin.
- 6.Withstanding voltage:800V AC/minute
- 7.Material:PA66 UL94V-0

8.Bill Of Part No.:

FU2507H-XP-X-HF

Pin:	Material Color
2	A : White
3	B : Black
4	C : Red
.	D : Orangr
.	E : Yellow
.	F : Green
.	.
.	.
.	.

DIM B±0.4

5.35

7.9

5.0


2PIN

9.Ordering Information & Dimensions

38.00	35.00	15	20.50	17.50	8
35.50	32.50	14	18.00	15.00	7
33.00	30.00	13	15.50	12.50	6
30.50	27.50	12	13.00	10.00	5
28.00	25.00	11	10.50	7.50	4
25.50	22.50	10	8.00	5.00	3
23.00	20.00	9	5.50	2.50	2
B	A	PIN	B	A	PIN

TOLERANCE

X.	X.XXX ±0.10
X.X ±0.30	
X.XX ±0.20	Angular ±2°



UNIT:
mm

DWG TYPE.

Customer Drawing

PART NO.

FU2507H-XP-X-HF

DRAWING NO.

C-FU2507H-XP-X-HF

APPROVED BY

CHECKED BY

DRAWN BY

PAGE
1OF1

SCALE
1: 1

REV.

A

东莞市福朗连接器制造有限公司
DONGGUAN FULANG CONNECTOR MANUFACTURING Co., LTD

TITLE. 2.5mm Pitch Wire To
Board Housing

A		For New Drawing	GuobaoLi	2017.12.22
REV.	ECN NO	REVISION RECORD	DRAW	DATE

6 QMI-P12-05-05