



BOARD IN SERIES


FU2008 2.00MM PITCH SERIES

Specifications:


- ◆ Rated Voltage: 125V AC,DC
- ◆ Rated Current: 2A AC,DC
- ◆ Withstand Voltage: 500V AC/minute
- ◆ Contact Resistance: 10mΩ Max.
- ◆ Insulation Resistance: 1000MΩ Min.
- ◆ Temperature Range: -40℃~+105℃
- ◆ Applicable Wire Range: AWG #26~#30
- ◆ Insulation O.D.: 1.40mmMax
- ◆ UL: Recognized No. E496848

ITEM	PART NO.	MATERIAL	POLES	Q'TY/REEL
Terminal	FU2008-T0P-XX	Phosphor bronze		10000PCS
HSG	FU2008H-XP-X-HF	Nylon 66 UL94V-0	02~1	1000PCS

FU2008-T0P-XX



FU2008H-XP-X-HF



CONNECTOR PRODUCT NUMBER

Terminal Ordering Code

FU2008 **T** **X** **X** **XX**

① — ② ③ ④ — ⑤

①: Series No.FU2008

②: Contact Terminal

③: Terminal Crimping Spec

0: Ordinary type

1: Low foot type

2: High foot type

④: Conductor Material Type

P: Phosphor Bronze

B: Brass

⑤: Conductor Surface Finish

B1: Bright-Sn

B2: Gold-Flash

HSG And Wafer Ordering Code

FU2008 **H** **XXP** **X** **HF**

① — ② — ③ — ④ — ⑤

①: Series No.FU2008

②: Conductor Type

H: Plastic Housing

③: Total Number of Contacts

XXP: Single Row

⑤: Halogen-free

④: Color

A: Black

B: Brown

C: Others