


BOARD IN SERIES

FU2011 2.00MM PITCH SERIES


Specifications:

- ◆ Rated Voltage: 250V AC,DC
- ◆ Rated Current: 1A AC,DC
- ◆ Withstand Voltage: 1000V AC/minute
- ◆ Contact Resistance: 20mΩ Max.
- ◆ Insulation Resistance: 500MΩ Min.
- ◆ Temperature Range: -40℃~+105℃
- ◆ Applicable Wire Range: AWG #26~#30
- ◆ Insulation O.D.: 1.40mmMax
- ◆ UL: Recognized No. E496848


ITEM	PART NO.	MATERIAL	POLES	Q'TY/REEL
Terminal	FU2011-T0B-XX	Brass		15000PCS
HSG	FU2011H-XP-X-HF	PBT UL94V-0	02~15	1000PCS



FU2011-T0B-XX



FU2011H-XP-X-HF



CONNECTOR PRODUCT NUMBER

Terminal Ordering Code

FU2011 **T** **X** **X** **XX**

① — ② ③ ④ — ⑤

①: Series No.FU2011

②: Contact Terminal

③: Terminal Crimping Spec

0 : Ordinary type

1 : Low foot type

2 : High foot type

④: Conductor Material Type

P: Phosphor Bronze

B: Brass

⑤: Conductor Surface Finish

B1: Bright-Sn

B2: Gold-Flash

HSG And Wafer Ordering Code

FU2011 **H** **XXP** **X** **HF**

① — ② ③ — ④ — ⑤

①: Series No.FU2011

②: Conductor Type

H: Plastic Housing

③: Total Number of Contacts

XXP: Single Row

⑤: Halogen-free

④: Color

A: Black

B: Brown

C: Others