



WIRE TO BOARD SERIES


FU2001, FU2002 2.0MM PITCH SERIES

Specifications:


- ◆ Rated Voltage: 125V AC, DC
- ◆ Rated Current: 2A AC, DC
- ◆ Withstand Voltage: 500V AC/minute
- ◆ Contact Resistance: 20mΩ Max.
- ◆ Insulation Resistance: 1000MΩ Min.
- ◆ Temperature Range: -40℃~+105℃
- ◆ Applicable Wire Range: AWG #24~#28
- ◆ Insulation O.D.: 1.15mmMax
- ◆ UL: Recognized No. E496848

ITEM	PART NO.	MATERIAL	POLES	Q'TY/REEL
Terminal	FU2001-T0P-B1	Phosphor bronze		10000PCS
	FU2002-T0P-B1	Phosphor bronze		10000PCS
HSG	FU2001H-XP-X-HF	Nylon 66 UL94V-0	02~10	1000PCS
	FU2002H-XP-X-HF	Nylon 66 UL94V-0	02~10	1000PCS


FU2001-T0P-B1




FU2001H-XP-X-HF



FU2002-T0P-B1



FU2002H-XP-X-HF



CONNECTOR PRODUCT NUMBER

Terminal Ordering Code

FU200X **T X X** **XX**

① — ② ③ ④ — ⑤

①: Series No. FU2001, 2002

②: Contact Terminal

③: Terminal Crimping Spec

0: Ordinary type
1: Low foot type
2: High foot type

④: Conductor Material Type

P: Phosphor Bronze
B: Brass

⑤: Conductor Surface Finish

B1: Bright-Sn
B2: Gold-Flash

HSG And Wafer Ordering Code

FU200X **H** **XXP** **X** **HF**

① — ② — ③ — ④ — ⑤

①: Series No. FU2001, 2002

②: Conductor Type

H: Plastic Housing

③: Total Number of Contacts

XXP: Single Row

⑤: Halogen-free

④: Color

A: Black
B: Brown
C: Others