


WIRE TO BOARD SERIES

FU6351, FU6352 6.35MM PITCH SERIES

Specifications:

- ◆ Rated Voltage: 600V AC, DC
- ◆ Rated Current: 19A AC, DC
- ◆ Withstand Voltage: 5000V AC/minute
- ◆ Contact Resistance: 10mΩ Max.
- ◆ Insulation Resistance: 1000MΩ Min.
- ◆ Temperature Range: -40℃~+105℃
- ◆ Applicable Wire Range: AWG #16~#20
- ◆ Insulation O.D.: 3.30mmMax
- ◆ UL: Recognized No. E496848

ITEM	PART NO.	MATERIAL	POLES	Q'TY/REEL
Terminal	FU6351-T0P-B1	Phosphor bronze		3500PCS
	FU6352-T0P-B1	Phosphor bronze		3500PCS
HSG	FU6351H-XxXP-X-HF	Nylon 66 UL94V-0	02~05	500PCS
	FU6352H-XxXP-X-HF	Nylon 66 UL94V-0	02~05	500PCS







FU6351-T0P-B1

FU6351H-XxXP-X-HF

FU6352-T0P-B1

FU6352H-XxxP-X-HF



CONNECTOR PRODUCT NUMBER

Terminal Ordering Code

FU635X T X X XX

① — ② ③ ④ — ⑤

①: Series No. FU6351, FU6352

②: Contact Terminal

③: Terminal Crimping Spec

0: Ordinary type
1: Low foot type
2: High foot type

④: Conductor Material Type

P: Phosphor Bronze
B: Brass

⑤: Conductor Surface Finish

B1: Bright-Sn
B2: Gold-Flash

HSG And Wafer Ordering Code

FU635X H XXP X HF

① — ② — ③ — ④ — ⑤

①: Series No. FU6351, FU6352

②: Conductor Type

H: Plastic Housing

③: Total Number of Contacts

XXP: Single Row
2xXXP: Dual Row

⑤: Halogen-free

④: Color

A: Black
B: Brown
C: Others